



FS-C2626MFP Color Multifunctional Printer

ECONOMICAL. ECOLOGICAL. ECOSYS TECHNOLOGY.

- Fast output speeds of 28 pages per minute
- Standard print, copy, scan and fax
- Newly designed color touch screen control panel
- ECOSYS® long life consumables reduce operating costs
- USB interface for convenient print-from and scan-to capability
- HyPAS™ capable for critical business applications





FS-C2626MFP



FS-C2626MFP standard configuration



FS-C2626MFP shown fully configured for optimal performance



Touch screen control panel for simple navigation and streamlined job execution

HyPAS™

Hybrid Platform for Advanced Solutions

Kyocera Mita America's objective is to manufacture superior products with a low Total Cost of Ownership (TCO) and minimize the impact on the environment. Kyocera's ECOSYS printers incorporate a patented long life drum which is separate from the toner container, eliminating the need to replace the drum when toner is depleted – and reducing landfill waste.

ECOSYS printers provide customers with a printing solution that incorporates long life consumables and one of the lowest costs per print. The operating costs of traditional cartridge-based printers can easily exceed many times the original purchase price during the life of the product. Evaluate your printer costs today.



Basic Specifications

Configuration	Color Multifunction Printer - Standard Copy, Print, Scan, and Black & White Fax
Pages Per Minute	Letter: 28 ppm; Legal: 23 ppm; A4: 26 ppm; Duplex: 13 ipm (Letter)
Warm-up Time	29 Seconds or Less
First Copy / Print Out Time	Black: 10 Seconds, Color: 12 Seconds / Black: 9.0 Seconds, Color: 10.5 Seconds
Resolution	600 x 600 dpi
Memory (Std / Max)	1 GB RAM / 2 GB RAM
Duplex	Standard Stackless
Electrical Requirements	120V, 60Hz, 9A; 220-240V, 50/60Hz, 4.8A
Typical Energy Consumption (TEC)	3.642 kWh/Week
Size / Weight	20.3" W x 21.7" D x 23.7" H / 85.1 lbs
Max Monthly Duty Cycle	65,000 Pages Per Month

Paper Supply

Standard Paper Sources	Standard 250 Sheet Paper Drawer, 50 Sheet Multi Purpose Tray
Optional Paper Sources	Up to two (2) optional 500 Sheet Paper Drawers can be added (PF-520 or PF-530)
Paper Capacity	Standard: 300 Sheets; Maximum: 1,300 Sheets
Paper Size	5.5" x 8.5" - 8.5" x 14" (Statement to Legal) via Drawers, 2.8" x 5.8" - 8.5" x 14" via MPT
Paper Weight	Standard Drawers and PF-520: 16 lb Bond - 90 lb Index (60 - 163gsm); MPT and PF-530: 16 lb Bond - 120 lb Index (60 - 220gsm)
Input Materials	Bond Paper, Recycled Paper, Transparencies, Labels, Glossy, Envelopes (print only)

Document Processor

Type / Capacity	Standard Reversing Automatic Document Processor / 50 Sheets (Letter)
Copy Scan Speed	35 ipm Black; 25 ipm Color
Acceptable Originals / Weights	Letter, Legal, A4 / Simplex: 13 - 32 lb Bond (50 - 120gsm), Duplex: 13 - 60 lb Index (50 - 110gsm)

Duplex

Paper Size	Letter, Legal, A4, Statement
Paper Weight	16 lb Bond- 90 lb Index (60 - 163gsm)
Duplex Modes	1:2; 2:2; 2:1

Copy Specifications

Image Mode	Text, Photo, Text/Photo, Auto, Graphic/Map, Printer Output, Manual
Continuous Copy	1 - 999 / Auto Reset to 1
Additional Copy Features	Auto Center, Magnification and Auto Paper Select, Combine Image, Auto Start, Priority Copy, 100 Department Codes, 20 Customizable User Logins, Job Programs
Magnification / Zoom	Full Size, 7 Reduction, 5 Enlargement Preset Ratios, 25 - 400% in 1% step increments
Document Box	Job Box for RAM Based Private Print, Removable Memory for Print-from/Scan-to USB

Printer Specifications

Controller	PowerPC 464 / 800MHz
PDLs/Emulations	PRESCRIBE, PCL6 (5e, XL), KPDL3 (PS3), XPS, Novell Print
Fonts	93 KPDL3, PCL6, 8 Vista, 1 Bitmap, 45 Barcodes, 1 PDF-417
Windows OS Compatibility	Windows 2000 / XP / 2003 / Vista / 2008 / 7
Mac OS Compatibility	Mac OS 10.x
UNIX OS Compatibility	Sun OS 4.1.x; Solaris 2.x; AIX; HP-UX (LPR)
Interfaces	Standard: 10/100/1000BaseTX, Hi-Speed USB 2.0, USB Host Interface
Network Print and Supported Protocols	TCP/IP, IPX/SPX, AppleTalk, NetBEUI, IPsec, HTTPS, LDAP over SSL, SNMPv3, Kerberos, NTLM, 802.1x
Drivers	KX Driver, Mini Driver, PPD for Mac, PPD for UNIX
Utilities	PRESCRIBE Utilities, PDF Direct Print, KMnet Admin, KMnet Viewer, Status Monitor, Command Center

Scan Specifications

Scan Type	Color and Black & White Scanner
Scan Resolutions	200, 300, 400, 600, 200 x 100, 200 x 400 dpi
Network Scan Speed	Mono: 300/200 dpi - 35 ipm Simplex; 18 ipm Duplex / 600 dpi - 25 ipm Simplex; 13 ipm Duplex Color: 300/200 dpi - 25 ipm Simplex; 13 ipm Duplex / 600 dpi - 13 ipm Simplex; 7 ipm Duplex
File Formats	TIFF, JPEG, XPS, PDF, PDF/A
Connectivity / Supported Protocols	10/100/1000BaseTX / TCP/IP; Hi-Speed USB 2.0
Scanning Functions	Scan to PC, Scan to e-Mail, Scan to FTP, Scan to USB, WSD Scan, Network TWAIN/WTA
Driver	TWAIN Driver, WIA Driver

Fax Specifications

Fax Type Compatibility	ITU-T Group3
Data Compression	MH / MR / MMR / JBIG
Fax Transmission Selection	Standard / Fine/ Photo
Fax Memory	3.5 MB
Transmission Speed / Modem	Less than 3 Seconds per page / 33.6 kbps
Fax Memory Capacity	256 Sheets
Network Fax Reception	Supports SMB/FTP/e-Mail protocols
Fax Functions	Duplex Transmission/Reception, Dual Access, One Touch Dial (100 numbers), FAX/TEL Switching, Broadcast, Quick Dial (200 numbers), Fax Reports

USB Host Interface

Type	Supports direct printing and scanning from USB Drive
Supported File Types	Print: PDF, TIFF, XPS Scan: PDF, JPEG, TIFF, XPS, PDF/A

Optional Paper Drawers

PF-520	
Paper Capacity	500 Sheets
Max Drawers	Up to two (2) PF-520 Drawers can be installed*
Paper Size	Letter, Legal, A4
Paper Weight	16 lb Bond - 90 lb Index (60 - 163gsm)
Size / Weight	15.4" W x 20.3" D x 4.6" H / 9.5 lbs

PF-530	
Paper Capacity	500 Sheets
Max Drawers	Up to two (2) PF-530 Drawers can be installed*
Paper Size	Letter, Legal, A4
Paper Weight	16 lb Bond - 120 lb Index (60 - 220gsm)
Size / Weight	15.4" W x 20.3" D x 4.6" H / 11.3 lbs

Additional Options

Memory	Optional 512 MB or 1 GB RAM
--------	-----------------------------

*Note: A maximum of two (2) optional Paper Drawers can be added

Specifications and design are subject to change without notice. For the latest on connectivity visit www.kyoceramita.com. All trademarks are the property of their respective owners.

Kyocera Mita America, Inc. Headquarters: 225 Sand Road, Fairfield, NJ 07004-0008, USA
©2011 Kyocera Mita America, Inc.
IC# 855D400320

